

## AC INDUCTION MOTOR FAMILY

### Series K037G264555725E AC Induction Geared TEFC Motor



Item:	Right Angle AC Gear Motor
Full Load Torque (In-Lbs):	85 In-Lbs
Input HP:	1/8 HP
Starting Torque (In-Lbs):	72 In-Lbs
Voltage (Vac):	115 Vac 60 Hz 105 Vac 50 Hz
Full Load Amps:	2.0 Amps
Capacitor (mfd):	15 mfd 370V (Not Supplied)
Speed (RPM):	29 RPM @ 60 Hz 24 RPM @ 50 Hz
Gear Ratio:	60:1
Rotation:	Reversible
Phase:	1 (Single Phase)
Overhung Load (Lb):	130 Lbs
Ambient Temp. Max (C/F):	40°C / 104°F
Enclosure Type:	Totally Enclosed Fan-Cooled (TEFC)
Motor Type:	Permanent Split Capacitor (PSC)
Insulation Class:	Class B
Thermal Protection:	None
Bearings:	Ball Bearing
Gears:	Worm, Hardened Steel; Forged Bronze Output Gear
Agency Compliance:	UL Recognized (E22922) CSA Certified (LR2459)
Note: Typical data subject to change without notification; Ratings shown are at 60 Hz unless noted. Gear motors are also operable at 105V, 50 Hz, with HP and RPM at 5/6 of the 60 Hz rating.	

#### Additional Info

- 115 and 105VAC Combined Permanent Split Capacitor Right-Angle Gearmotors
- Gearcase: Zinc Alloy
- Lubrication: TENV models grease-filled; TEFC models oil-filled
- Gears: TENV models Worm, Hardened Steel, Phenolic Output Gear; TEFC models Worm, Hardened Steel; Forged Bronze Output Gear
- Bearings: Ball Bearing on case and motor
- Mounting: All-position except input motor shaft up
- 60/50 Hz
- UL Recognized and CSA Certified

